

Digital pH measuring and regulating system, for private, public and commercial pools.

- > Simple and intuitive programming menu (password protected)
- > ENCODER system with easy friendly software interface
- > Electronic timeout alarm to avoid pH overdosing
- > Suction reed with pH level probe (optional)
- > Auto calibration with 2 buffers or DPD
- > Very broad measuring range (0-13.8)
- > Highly accurate pH scale ±0.1
- > Progressive pH injection
- > Screwless clamp saddles
- > Long life pH electrode
- > Buffers included

| Specifications |

Power Supply: 220/240Vac 50/60Hz

Injection Pump: Peristaltic Injection Flow: 0 - 45 l/h Injection Pressure: 1 Bar

Water Temperature Range:12°C to 40°C Room Temperature: Tested at 50°C

Buffers: 4 & 7 Warranty: 2 Years



w165mm X H145mm X L85mm



pH Scale



pH Precision



Encoder



Alarm



EL Probe



Warranty













Accessories

SANUS MODELS

		<u> </u>
CODE 100000722 ^A	MODEL SANUS	PRESSURE FLOW I/h - Bar 4.5-2
CODE 100000723 ^A	MODEL SANUS PLUS	PRESSURE FLOW I/h - Bar 6-7
CODE 100000991 ^A	DESCRIPTION OF BUOY Tank with Aspiration Tube	